

# DEVICEMASTER DIN Rail

## ETHERNET DEVICE SERVERS

### PRODUCT COMPARISON CHART



Ethernet Device Servers	DM-2101 (99600-2)	DM-2201 (99603-3)	DM-2202 (99480-0)	DM-2102 (99550-0)	DM-2402 (99481-7)	DM-2302 (99560-9)	DM-2304 (99610-1)
<b>HARDWARE</b>							
Number of Ports: 10/100BASE-TX	1	1	1	1	2	2	4
Number of Serial Ports	1 x RS-232/422/485	1 x RS-232/422/485	2 x RS-232/422/485	2 x RS-232/422/485	2 x RS-232/422/485	2 x RS-232/422/485	4 x RS-232/422/485
Serial Baud Rate	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230 Kbps
Serial Interface	DB9M	Terminal Block	Screw Terminal	DB9M	Screw Terminal	DB9M	DB9M
Power Input	5-30VDC Terminal (1.5W)	5-30VDC	5-30VDC Terminal (1.5W)	5-30VDC Terminal (1.6W)	5-30VDC Terminal (2W)	5-30VDC Terminal (2W)	5-30VDC
Included Power Supply	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Serial Surge Protect	25KV	25KV	25KV	25KV	25KV	25KV	25KV
<b>ENVIRONMENTAL</b>							
MTBF	61.4 Years	61.4 Years	58.57 Years	58.57 Years	45.66 Years	49.5 Years	42.3 Years
Enclosure	UL94-V0 Plastic	UL94-V0 Plastic	UL94-V0 Plastic	UL94-V0 Plastic	UL94-V0 Plastic	UL94-V0 Plastic	UL94-V0 Plastic
Dimension	4.52" x 3.9" x 0.9"	4.7" x 3.9" x 0.9"	4.37" x 3.9" x 0.89"	4.6" x 3.9" x 0.9"	4.37" x 3.9" x 1.78"	4.6" x 3.9" x 1.8"	4.6" x 3.9" x 1.8"
Operating Temperature	-40°C to 75°C	-40°C to 75°C	-40°C to 75°C	-40°C to 75°C	-40°C to 75°C	-40°C to 75°C	-40° to 75°C
Installation Method	DIN rail	DIN rail	DIN rail	DIN rail	DIN rail	DIN rail	DIN rail
<b>SUPPORTED DEVICE DRIVERS</b>							
Microsoft® Windows® XP through Windows 2019	Yes >>						
Linux							
<b>SOFTWARE</b>							
TCP, UDP Socket							
PortVision® Remote Monitoring & Management							
Web-based Configuration	Yes >>						
SSL & SSH Encryption							
E-mail Event Notification							
<b>CERTIFICATIONS</b>							
CE/FCC/UL/RoHS2	Yes	Yes	Yes	Yes	Yes	Yes	Yes
NEMA TS2	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years