

DEVICEMASTER DIN rail

ETHERNET DEVICE SERVERS

PRODUCT COMPARISON CHART



Ethernet Device Servers	DM-2101 (99600-2)	DM-2201 (99603-3)	DM-2202 (99480-0)	DM-2102 (99550-0)	DM-2402 (99481-7)	DM-2302 (99560-9)	DM-2304 (99610-1)
HARDWARE							
Number of Ports: 10/100BASE-TX	1	1	1	1	2	2	4
Number of Serial Ports	1 x RS-232/422/485	1 x RS-232/422/485	2 x RS-232/422/485	2 x RS-232/422/485	2 x RS-232/422/485	2 x RS-232/422/485	4 x RS-232/422/485
Serial Baud Rate	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230.4Kbps	300bps to 230 Kbps
Serial Interface	DB9M	Terminal Block	Screw Terminal	DB9M	Screw Terminal	DB9M	DB9M
Power Input	5-30VDC Terminal (1.5W)	5-30VDC	5-30VDC Terminal (1.5W)	2 x 6-30VDC Terminal (1.6W)	5-30VDC Terminal (2W)	2 x 6-30VDC Terminal (2W)	5-30VDC
Included Power Supply	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Serial Surge Protect	25KV	25KV	25KV	25KV	25KV	25KV	25KV
ENVIRONMENTAL							
MTBF	61.4 Years	61.4 Years	58.57 Years	58.57 Years	45.66 Years	49.5 Years	42.3 Years
Enclosure	UL94-V0 Plastic	UL94-V0 Plastic	UL94-V0 Plastic	UL94-V0 Plastic	UL94-V0 Plastic	UL94-V0 Plastic	UL94-V0 Plastic
Dimension	4.52" x 3.9" x 0.9"	4.7" x 3.9" x 0.9"	4.37" x 3.9" x 0.89"	4.6" x 3.9" x 0.9"	4.37" x 3.9" x 1.78"	4.6" x 3.9" x 1.8"	4.6" x 3.9" x 1.8"
Operating Temperature	-40 to 85° C	-40°C to 85°C	-37° to 74°C	-37° to 74°C	-37° to 74°C	-37° to 74°C	-40° to 75°C
Installation Method	DIN rail	DIN rail	DIN rail	DIN rail	DIN rail	DIN rail	DIN rail
SUPPORTED DEVICE DRIVERS							
Windows 2000/Server 2003/XP	Yes >>						
Windows Server 2008							
Windows Vista							
Windows 7							
Linux							
SOFTWARE							
TCP, UDP Socket	Yes >>						
PortVision® Remote Monitoring & Management							
Web-based Configuration							
SSL & SSH Encryption							
E-mail Event Notification							
CERTIFICATIONS							
CE/FCC/UL/RoHS2	Yes	Yes	Yes	Yes	Yes	Yes	Yes
NEMA TS2	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years	5 Years