



RocketLinx® ES8108

Part Number: 32055-5



KEY FEATURES AND BENEFITS::

- 8-Port 10/100BASE-TX Industrial Fast Ethernet Switch
- 2.0Gbps Switch Fabric with excellent data exchange performance
- QoS for packet forwarding precedence
- Broadcast storm packet filtering
- Supports 1.5KV Hi-Pot isolation protection
- Redundant dual power input 10 to 60VDC
- Port and Power Event Alarm
- Compact aluminum case with IP31 grade protection
- -25° to 70°C operating temperature for harsh environments
- DIN rail installation
- Meets heavy industrial EMI/EMC regulations
- RoHS2 compliant under CE
- VLAN tag priority support

PRODUCT DESCRIPTION::

The RocketLinx ES8108 is Control's 8-port Fast Ethernet industrial switch featuring a 2.0Gbps Packet Switch engine with packet forwarding and filtering mechanisms to meet industrial communications standards. It provides packet forwarding capabilities to handle 64 to 1522 byte long packet sizes in two priority queues to optimize data forwarding performance. Broadcast storm filtering and flow control functions ensure data delivery free of traffic congestion.

For installation in harsh or industrial environments, the ES8108 is equipped with two redundant power inputs, features a rugged IP31 grade housing, and operates within a broad -25° to 70°C temperature range. For ease-of-maintenance, the ES8108 has alarm output relays for port link and power events to assist engineers with on-site monitoring.

RocketLinx Reliability

The RocketLinx ES8108 includes dual power inputs that can operate on 10 to 60VDC. Dual power inputs and built-in reverse power polarity protection are designed as the redundant power system to ensure power continuity. With the 1.5KV Hi-Pot isolation protection, CE/FCC/UL regulatory approvals, and a 5-year warranty, the RocketLinx ES8108 is the ideal switch solution for deployment in harsh and industrial environments.



ROCKETLINX SPECIFICATIONS ::

HARDWARE

Bus Interface Specification	10/100 BASE-TX
Enclosure	IP31 grade compact aluminum metal case Drop waterproof and dustproof
Installation Method	DIN rail
LED Indicators	Power 1, Power 2, port/power alarm, RJ-45 port link/activity
Dimensions	4.72" x 2.17" x 4.25" 120 x 55 x 108 mm
Product Weight	1.20 lbs 0.54 kg

TECHNOLOGY

Standard	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX
Switch Technology	2.0Gbps switch fabric, store and forward technology
Flow Control	IEEE 802.3x Flow Control
QoS (Quality of Service)	IEEE 802.1Q Quality of Service IEEE 802.1p Class of Service

PERFORMANCE

Aggregate System Throughput	1.49Mbps
Number of MAC Address	2K
Packet Buffer Memory	448Kbits
Transfer Packet Size	1522 bytes
Broadcast Storm Control	Default enabled
Broadcast Traffic Threshold	Default enabled 100Mbps 200 packets/sec. 10Mbps 20 packets/sec.
Class of Service	2 packet forwarding @ queues High Queue (4-7) Low Queue (0-3)
Quality of Service	Default enabled, supports VLAN tag priority, IPv4 packet precedence
Event Alarm	Both port and event alarm; Enabled by 9-pin DIP switch

ELECTRICAL SPECIFICATIONS

Device	DC Input Voltage 10 to 60VDC Current Consumption (+24VDC) 0.125A @ 24VDC
Power Consumption (max)	3W
Power Connector	1
Power Connector Type	6-pin screw terminal block
Power Input Redundancy	Dual redundant independent power inputs
Reverse Polarity Protection	Yes
Power Alarm Relay	Alarm for power failure notification
Relay	0.5A Max. @ 24VDC

ENVIRONMENTAL SPECIFICATIONS

Air temperature	System On -25° to 70°C System Off -40° to 85°C
Operating Humidity	Non-condensing 0% to 95%
MTBF (Mean Time Between Failures)	146.6 years

ETHERNET SPECIFICATIONS

Connector Type	RJ45
Number of Ports	8
Ethernet Cable Type	Cat 3, Cat 4, Cat 5, Cat 5e (UTP or STP)
Standard	10/100BASE-TX, auto MDI/MDI-X, auto negotiation
Link Distance	100 Meters
Port Alarm Relay	Alarm relay for port failure notification
Relay	0.5A Max. @ 24VDC

EXPORT INFORMATION

Packaged Shipping Weight	1.55lbs 0.70kg
Package Dimensions	7" x 7.75" x 3.125" 178 x 197 x 79 mm
UPC Code	7-56727-32055-5
ECCN	5A991
Schedule B Number	8517.62.0050

REGULATORY APPROVALS

Emissions	Heavy Industrial Equip. Std. IEC/EN61000-6-4 CISPR 16-1-2/-2-1/-2-3/22 FCC Part 15 Subpart B Class A
Immunity	European Standard EN55024 IEC 1000-4-2/EN61000-4-2: ESD IEC 1000-4-3/EN61000-4-3: RF IEC 1000-4-4/EN61000-4-4: Fast Transient IEC 1000-4-5/EN61000-4-5: Surge IEC 1000-4-6/EN61000-4-6: Conducted Disturbance IEC 1000-4-8/EN61000-4-8: Magnetic Field
Safety	IEC 60950/EN60950 (LISTED) CSA C22.2 60950/UL60950 Third Edition
Other	RoHS2 compliant under CE
Regulatory Approvals	



RECOMMENDED PRODUCTS ::

32100-2	Power Supply PS1020 Universal (24V, 20W, Din Rail)
32101-9	Power Supply PS1060 Universal (24V, 60W, Din Rail)
32102-6	Power Supply PS1100 Universal



Warranty Information
Control offers a 30-day satisfaction guarantee and 5-year limited warranty.

Sales Support
+1.763.957.6000
sales@comtrol.com

Technical Support
+1.763.957.6000
www.comtrol.com/support

Email, FTP, and Web Support
info@comtrol.com
ftp.comtrol.com
www.comtrol.com